



## **FHC Venice Series 180 Degree Glass to Glass Hinge - Brushed Nickel**

**Item No.** VEN180BN

### **Features, Advantages, and Benefits**

- HD Square Profile Glass to Glass 180 Deg Hinge
- Designed For 3/8"-1/2" (10 mm to 12 mm) Tempered Glass
- Heavy Duty Design For Wider and Heavier Doors
- Self-Centering within 15 Degrees of Closing Position

- Commonly used in Residential Bath and Commercial Hotel Applications
- Reversible 5 Deg Pivot Pin For Jobs Requiring a Positive Closing Position
- Many Popular Finishes to Select From

**Description:**

## Glass Specifications

MAXIMUM DOOR CAPACITY	3/8" (10 mm) GLASS	Approx. 5 lb/ft <sup>2</sup>	
	1/2" (12 mm) GLASS	Approx. 6.4 lb/ft <sup>2</sup>	
DOOR WEIGHT	DOOR WIDTH	Using 2 Hinges	
		110 LBS (50 kg)	36" (914 mm)
		Using 3 Hinges	140 LBS. (64 kg)
		36" (914 mm)	36" (914 mm)

**NOTE:** Do Not Exceed either maximum weight or width when choosing proper quantity of hinges.

**Gasket Specifications**  
 For 3/8" (10 mm) Glass: Use One Thick Gasket On Each Side  
 For 1/2" (12 mm) Glass: Use One Thin Gasket On Each Side

**Glass Instructions**  
 Only use tempered safety glass. To prevent damage to the hinge finish during installation, do not use power tools when installing these hinges.

**Overview**  
 The Venice Series Hinge has a dual degree pivot pin. It comes factory set at 90 degrees for normal door closing applications. There is also a secondary setting on the hinge pivot pin that can be field adjusted to allow an additional 5 degrees of closing for jobs that require a firmer positive position against a jamb or seal.

**Care & Cleaning Guidelines**  
 For best results, keep the following recommendations in mind when caring for your FHC shower door hardware. Your shower door should be dried daily with a soft towel or cloth to ensure its original finish. Do not use harsh cleaners or chemicals on the hardware, as many of the components are coated with a clear lacquer that will become damaged beyond repair. Always test your cleaning solution in an inconspicuous area prior to cleaning the entire hardware surface. Wipe surfaces clean using a soft, dampened cloth or sponge, and rinse completely with warm water immediately after applying the cleaning solution. Use only small amounts of liquid, gentle, cleaner. Never use abrasive

products, sponges, or wire scrub brushes while cleaning hardware.

## Maintenance

FHC's hinges come factory greased for a silent, hassle-free experience. If there is any noticeable squeaking that occurs after installation it is recommended to apply a few drops of (3 in 1) multi-purpose oil to the hinge, at the nylon washer/pivot location. The lubricant will penetrate the hinge crevices, reducing friction, cleaning grime, and/or buildup. Spray lubricants are prohibited. If, for some reason, the hinge is disassembled during maintenance, use a small amount of white lithium grease to lubricate the interior hinge components.

## Material/Construction

Solid Brass

