



FHC Keyed Child-Proof Sash Lock - 2" Hole Centers - Diecast Zinc - Polished Brass - (Single Pack)

Item No. F2534

Features, Advantages, and Benefits

- For use on horizontal and vertical sliding windows constructed of aluminum, vinyl, and wood

- Universal design allows these locks to be mounted on sliding sash where their checkrails rest flush when closed
- Keyed sash locks help child-proof sliding windows increasing the safety and security of the home or office
- Limits disengagement of locks and opening of sliding windows to key-only access
- Both the lock bodies and keepers have mounting holes spaced apart at 2 inches, on center
- Constructed of durable diecast zinc and come in a polished brass-plated finish
- Both the locks and keepers install easily with a simple handheld Phillips screwdriver

Description: Overview Do you need a more secure way to child-proof your sliding windows? These keyed-locking sash locks help add peace of mind by increasing the safety of any unmonitored room with sliding windows. They are constructed of diecast zinc and come in a beautiful, polished brass-plated finish, and only with their keys can the locks be disengaged to allow for opening of windows. These locks feature a universal design that allows them to be mounted on most vertical single-hung and double-hung sliding windows, in addition to those that slide horizontally. Depending on the size of the sash, these locks can be used as singles or pairs, and they can be installed on both left and right horizontal sliding sash. Each set contains two keys, one lock and keeper, and the installation fasteners. Installation of these sash locks is easy and can be done with a simple handheld Phillips head screwdriver. Other design features include a 5/8 inch wide keeper, 2 inch mounting hole centers (distance between each mounting hole measured from center to center of holes), and industry standard finish to match other existing hardware in the home or office. These keyed sash locks can be mounted on any sliding window where the checkrails of both the inner and outer sash rest flush, to include sliding windows constructed of aluminum, wood and vinyl. Only with the key inserted into the lock can the thumbturn swivel to open or close. Removing the key will lock the device in whichever position that the thumbturn is facing, either open or closed. Compare the style and dimensions of this lock to those required on your sliding windows and order yours today.