



FHC Safety Spring Door Closer - Easy To Install To Convert Hinged Doors To Self-Closing - Diecast Construction - 4-1/4" Brown - Non-Handed (Single Pack)

Item No. KC17HD

Features, Advantages, and Benefits

- **EASY DIY PROJECT** – Thanks to these Prime-Line KC17HD safety spring door closers, your next to-do is quick and easy. Use these door closers to convert hinged doors to self-closing ones.
- **INCLUDES** – (1) Surface mounted spring-loaded door closer, tensioning rod, slide plate and hole plugs to cover adjustment holes in closer body after desired tension has been set.
- **EASY INSTALLATION** – With a closer and plastic slide plate being surface mounted, installation is a breeze. This spring door closer can generate up to 150 pounds of closing force, and can be used on both left and right-handed doors.
- **ADJUSTABLE TENSION** – Easily adjust the tension on this safety spring door closer. These closers also feature adjustable closing speed.
- **PRODUCT INFO** – This safety spring door closer features a non-handed design and brown painted finish to complement any style door. 1 inch wide base, 4-1/4 inch hole center spacing and 4-3/4 inch arm.

Description: Overview Convert your hinged door into a self-closing one with the Prime-Line KC17HD Safety Spring Door Closer. Installation is a breeze thanks to the closer and plastic slide plate being surface mounted. Use this spring door closer on any door, it has 150 pounds of closing force. It can also be used on both left and right-handed doors. The door closers feature an adjustable closing force and speed. Constructed of diecast materials with a brown painted finish, this safety spring door closer can complement any style door. They are U.L. listed with a ½ hour fire rating and have a 1 inch wide base, 4-1/4 inch hole center spacing and 4-3/4 inch arm. These closers operate in a pushing-closed manner, rather than in a pulling-closed method, and they do not have a hold open feature. The closer arm of this safety spring closer has the ability to swing a full 180 degrees, but once it is mounted in place, the door's distance of swing will be reduced to the point of where it makes contact with the bullet-shaped housing of the closer. All fasteners and installation instructions are included with this item. Be sure to view the manufacturer's How-To Installation Video also linked to this page. Do not overtighten, turning past 4 hole positions will cause this item to fail.