

FHC S450 Series RTV Neutral Cure Silicone - Clear

Item No. S450C

Features, Advantages, and Benefits

- Superior Adhesion to Kynar Coated Materials
- Excellent Adhesion To Glass - Professional Grade
- Window and Door Approved
- UV Resistant / Non-Yellowing
- Available in Five Colors
- Compatible for Insulated Glass and Laminated Glass with SentryGlass® Interlayer
- Neutral Cure Sealant, Low Odor Formula AAMA Approved

Description: <h2>Overview</h2><p>S450 is a one component, non-sag, permanently flexible, neutral cure sealant. The product is engineered to deliver excellent adhesion to vinyl, glass, aluminum, wood, sheet metal, and most common building materials, without need for a primer. The product is an ideal fit for applications where there is a lack of moisture to aid the curing process.</p><h2>Material/Construction</h2><p>Meets ASTM C-920, Type S, Grade NS, Class 25, Use NT, M, G, A, O; TT-S-00230C & TT-S-001534A (COM-NBS) VOC: 3.47%, UV Resistance: Excellent, Movement: +/- 25% Hardness: (Shore A) 20 +/-25%, Peel Strength: 19 psi, Tensile Strength: 375 psi, Staining: None, Service Temperature: - 40 deg. F to 450 deg. F</p><h2>Hazard Statement</h2><p>Classification: This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) Skin sensitization: Category 1 Emergency Overview: Signal word - Warning Hazard Statements: May cause an allergic skin reaction Appearance: Varies Physical State: Paste Liquid Odor: Mild Precautionary Statements - Prevention Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves</p><h2>Surface Preparation</h2><p>The substrate must be clean, dry, frost-free, sound, and free of any oils, greases, incompatible sealers, paints, or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.</p><h2>How to Use</h2><p>For best results, ensure surface is clean, dry, and free of oil and grease. Cut nozzle to desired bead size, puncture inner seal. Apply with a caulking gun, forcing sealant onto the substrate, then tool if needed. Clean excess material with mineral spirits or similar solvent.</p><h2>Prevention</h2><p>Wash face, hands and any exposed skin thoroughly

after handling. Wear Personal Protective Equipment (PPE) like protective gloves, protective clothing, and

Precautions

IF ON SKIN: Wash thoroughly with soap and water. If skin irritates or rash occurs, get medical attention. Remove contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do; continue rinsing. If eye irritation persists, get medical attention. IF SWALLOWED: Immediately call a Poison Center or doctor. DO NOT induce vomiting.

Storage

Material is to be stored under controlled dry environment (below 75deg F). Use within 12 months from date of manufacture. For best results, keep material in tightly closed containers when not in use. Do not freeze.

Included With

Twist-On Nozzle