



FHC Sash Lock - 1-3/4 And 1-1/2" Hole Centers - Fits Single/Double Hung Wood Windows - Steel W/Diecast Lever - Bright Brass-Plated - (Single Pack)

Item No. U9924

Features, Advantages, and Benefits

- For use on older vertical sliding windows constructed of wood
- These locks mount on the check (or “meeting”) rails of single and double hung sash where their checkrails rest flush when closed
- Replacing loose-fitting, worn or missing sash locks can help restore and increase the safety and security of the home or office
- Features cam-type locking mechanism designed to grab and pull the keeper and meeting rails firmly together, providing tighter seals and increased security
- Lock has 1-3/4 inch mounting hole centers, keeper has mounting holes spaced apart at 1-1/2 inches, on center
- Constructed of steel and diecast zinc and comes in a bright brass-plated finish
- Both the locks and keepers can be installed with a simple handheld Phillips screwdriver

Description: Overview Do you have vertical sliding wood windows with loose-fitting, worn or missing locks? Besides adding a “new look” to your windows with a fresh set of locking hardware, these sash locks can help add peace of mind by restoring the security features on vertical sliding windows. These locks mount on wooden single-hung and double-hung vertical sliding windows. Each lock features a cam-type mechanism that is designed to draw the keeper in firmly towards the lock, providing your windows with tighter seals, better weatherizing, and increased security. They are constructed of stamped steel lock bases and keepers and feature diecast zinc levers. Each come in a corrosion-resistant, industry standard bright brass-plated finish to match other existing hardware that may already be in the home. Depending on the size of the sash, these locks can be used as singles or in pairs. Each set includes one lock and keeper, installation fasteners and simple instructions. Installation of these sash locks is easy and can be done with a simple handheld Phillips head screwdriver. Other design features include a low-profile keeper, cam-action fastening, 1-3/4 inch mounting hole centers on the lock, and 1-1/2 hole centers on the keeper. These sash locks are for use on older vertical sliding wood windows where the checkrails (also known as “meeting rails”) of both the inner and outer sash rest flush. Compare the style and dimensions of this lock to those required on your sliding windows and order yours today.