

FHC Square 90 Degree Glass Clamp - Oil Rubbed Bronze

Item No. CSU900RBM

Features, Advantages, and Benefits

- Fixed 90 Degree Glass to Glass Clamp
- Designed For 3/8"-1/2" (10 mm to 12 mm) Tempered Glass
- Designed to Secure Fixed 90 Degree Glass Panel Corners for Frameless Shower Applications
- Requires One 3/4" Dia Hole Drilled in Each Glass Panel
- Commonly used in Residential Bath and Commercial Hotel Applications
- Works with Mitered Corner or Overlapping Glass

Description: <h2>Gasket Specifications</h2><p>For 3/8" (10 mm) Glass: Use One Thick Gasket On Each Side For 1/2" (12 mm) Glass: Use One Thin Gasket On Each Side</p>

<h2>Glass Instructions</h2><p>Only use tempered safety glass. To prevent damage to the hinge finish during installation, do not use power tools when installing these hinges. </p><h2>Overview</h2><p>FHC 90 Degree Glass to Glass Square Profile Clamps are designed for corner fixed glass panel conditions. Allow a 1/16" (1.5mm) clearance between the glass edges per the provided glass fabrication template. Use FHC Tru-Clear silicone to provide a water-tight seal after clamp installation.</p><h2>Care & Cleaning Guidelines</h2><p>For best results, keep the following recommendations in mind when caring for your FHC shower door hardware. Your shower door should be dried daily with a soft towel or cloth to ensure its original finish. Do not use harsh cleaners or chemicals on the hardware, as many of the components are coated with a clear lacquer that will become damaged beyond repair. Always test your cleaning solution in an inconspicuous area prior to cleaning the entire hardware surface. Wipe surfaces clean using a soft, dampened cloth or sponge, and rinse completely with warm water immediately after applying the cleaning solution. Use only small amounts of liquid, gentle, cleaner. Never use abrasive products, sponges, or wire scrub brushes while cleaning hardware.</p>

<h2>Material/Construction</h2><p>High Quality Plated Solid Brass</p>