



## **FHC Premium Shower Door Sliding Kit for 3/8" Glass 60" X 72"**

**Item No.** PDK38

### **Features, Advantages, and Benefits**

- Designed for use with 3/8" (10mm) Tempered Glass
- Each Hanger Bracket Requires (1) 1/2" Dia Hole
- 3-3/4" Tall Curved Profile Header Track
- Stock Size Kits: 60" Wide X 72" Field Cut to Size

- One Standard Size Fits Most Applications
- Precision Bearings and Wheels Offer a Quiet Glide Experience
- Offered in Four Popular Architectural Finishes

**Description:**

## Glass Instructions

Only use 3/8" (10mm) tempered safety glass. To prevent damage to the shower unit and fitting finish during installation, use FHC's securing/protection tape during installation

## Overview

Our PDK Premium Series Frameless Sliding Shower Door Kits offer a beautiful architectural design, that maintains a brilliant, low-profile frameless look, using 3/8" (10mm) tempered glazing. Each top hanger bracket requires one 1/2" (6 mm) diameter hole for mounting. Precision bearings and wheels offer a quiet glide experience. One standard size fits most applications. Available Stock Size: 60" W x 72" H (1.52 x 1.83 m). PDK kits are offered with curved header, and vertical metal jambs and sill for, inline applications. Kits with fixed panels are not available.

## Care & Cleaning Guidelines

For best results, keep the following recommendations in mind when caring for your FHC shower door hardware. Your shower door should be dried daily with a soft towel or cloth to ensure its original finish. Do not use harsh cleaners or chemicals on the hardware, as many of the components are coated with a clear lacquer that will become damaged beyond repair. Always test your cleaning solution in an inconspicuous area prior to cleaning the entire hardware surface. Wipe surfaces clean using a soft, dampened cloth or sponge, and rinse completely with warm water immediately after applying the cleaning solution. Use only small amounts of liquid, gentle, cleaner. Never use abrasive products, sponges, or wire scrub brushes while cleaning

hardware.

## Maintenance

FHC's Sliding Shower Door Kits have precision bearing and wheels that come factory greased for a silent, hassle-free experience. If there is any noticeable squeaking that occurs after installation it is recommended to apply a few drops of (3 in 1) multi-purpose oil to the precision bearings. The lubricant will penetrate, reducing friction, cleaning grime, and/or buildup. Spray lubricants are prohibited.

## Material/Construction

Aluminum & Brass Construction

## How to Use

Refer to FHC's Installation Instructions for Step by Step Installations Guidelines, Quick Metal Cutting Formula, and Glass Sizing

Deductions. 

## Included With

(1) Head Track 61" (1549 mm) Length, (1) Sill Track 61" (1549 mm) Length, (2) Vertical Jambs 70-3/8" (1787 mm) Length (1) Towel Bar Single-Sided 24" (610 mm) Center-to-Center, (1) Back-to-Back Pull Knob, (1) Bottom Guide, (1) Vinyl Strip for Sill, (4) Jamb Bumpers / Guides, and (4) Glass Hanger Brackets / Rollers.

