



FHC Classic Series Tub Door Sliding Kit for 1/4" Glass 60" X 72"

Item No. CDK14

Features, Advantages, and Benefits

- No Glass Fabrication Required for Hanger Brackets
- Designed for use with 1/4" (6mm) Tempered Glass
- Not Designed for Use with Textured Glass
- 2-9/16" Tall Low Profile Curved or Flat Reversible Header Track

- Stock Size Kits: 60" Wide X 72" Field Cut to Size
- One Standard Size Fits Most Applications
- Precision Bearings and Wheels Offer a Quiet Glide Experience
- Offered in Four Popular Architectural Finishes

Description:

Glass Instructions

Only use 1/4" (6mm) tempered safety glass. To prevent damage to the shower unit and fitting finish during installation, use FHC's securing/protection tape during installation

Overview

Our CDK Classic Series Frameless Sliding Shower Door Kits offer a cost-effective engineered design, that maintains a brilliant, low-profile frameless look, using 1/4" (6mm) tempered glazing. The top hangers clamp to the glass and do not require glass fabrication. Precision bearings and wheels offer a quiet glide experience. One standard size fits most applications. Available Stock Size: 60" W x 72" H (1.52 x 1.83 m). CDK kits are offered with a slim line header, and vertical metal jambs and sill for, inline applications. Kits with fixed panels are not available.

Care & Cleaning Guidelines

For best results, keep the following recommendations in mind when caring for your FHC shower door hardware. Your shower door should be dried daily with a soft towel or cloth to ensure its original finish. Do not use harsh cleaners or chemicals on the hardware, as many of the components are coated with a clear lacquer that will become damaged beyond repair. Always test your cleaning solution in an inconspicuous area prior to cleaning the entire hardware surface. Wipe surfaces clean using a soft, dampened cloth or sponge, and rinse completely with warm water immediately after applying the cleaning solution. Use only small amounts of liquid, gentle, cleaner. Never use abrasive products, sponges, or wire scrub brushes while cleaning hardware.

Maintenance

FHC's Sliding Shower Door Kits have precision bearing and wheels that come factory greased for a silent, hassle-free experience. If there is any noticeable squeaking that occurs after installation it is recommended to apply a few drops of (3 in 1) multi-purpose oil to the precision bearings. The lubricant will penetrate, reducing friction, cleaning grime, and/or buildup. Spray lubricants are prohibited.

Material/Construction

Aluminum & Brass Construction

How to Use

Refer to FHC's Installation Instructions for Step by Step Installations Guidelines, Quick Metal Cutting Formula, and Glass Sizing Deductions.

Included With

(1) Head Track 61" (1549 mm) Length, (1) Sill Track 61" (1549 mm) Length, (2) Vertical Jambs 70-3/8" (1787 mm) Length (1) Towel Bar Single-Sided 24" (610 mm) Center-to-Center, (1) Back-to-Back Pull Knob, (1) Bottom Guide, (1) Vinyl Strip for Sill, (4) Jamb Bumpers / Guides, and (4) Glass Hanger Brackets / Rollers.

