

FHC Pacifica Sliding Kit 3/8" Glass

Item No. PSK84

Features, Advantages, and Benefits

- Designed for use with 3/8" (10mm) Tempered Glass
- Sliding Panel and Fixed Panel Reversible Configuration
- Item No. PSK90 90° Adapter Sold Separately
- Maximum Weight for Sliding Door is 90 lbs.
- 84" Maximum Opening Width, Field Cut to Size
- Each Glass Hanger Bracket Requires (1) 3/4" Diameter Hole

- Modern 1-11/16" Diameter Round Profile Header
- One Standard Size Fits Most Applications
- Precision Bearings and Wheels Offer a Quiet Glide Experience

Description: <h2>Glass Instructions</h2>Only use 3/8" (10mm) tempered safety glass. To prevent damage to the shower unit and fitting finish during installation, use FHC's securing/protection tape during installation <h2>Overview</h2>Our Pacifica Series Frameless Sliding Shower Door Kits offer a modern sleek design and maintain a low-profile header and glass hangers that's engineered for use with 3/8" (10mm) tempered glazing. Each top hanger requires one 3/4" (19mm) diameter hole in the glass for proper mounting. Precision bearings and wheels also offer a quiet glade experience. One standard size fits most 180 degree inline applications. Our in stock 84" wide kits can be cut to size. Pacifica kits include head track, glass hangers, roller stops, floor guide, wall mount hangers, fixed panel glass attachments, threshold, and wall L-seal polycarbonate.<h2>Care & Cleaning Guidelines</h2>For best results, keep the following recommendations in mind when caring for your FHC shower door hardware. Your shower door should be dried daily with a soft towel or cloth to ensure its original finish. Do not use harsh cleaners or chemicals on the hardware, as many of the components are coated with a clear lacguer that will become damaged beyond repair. Always test your cleaning solution in an inconspicuous area prior to cleaning the entire hardware surface. Wipe surfaces clean using a soft, dampened cloth or sponge, and rinse completely with warm water immediately after applying the cleaning solution. Use only small amounts of liquid, gentle, cleaner. Never use abrasive products, sponges, or wire scrub brushes while cleaning hardware.<h2>Maintenance</h2>FHC's Sliding Shower Door Kits have precision bearing and wheels that come factory greased for a silent, hasslefree experience. If there is any noticeable squeaking that occurs after installation it is recommended to apply a few drops of (3 in 1) multi-purpose oil to the precision bearings. The lubricant will penetrate, reducing friction, cleaning grime, and/or buildup. Spray lubricants are prohibited.

<h2>Material/Construction</h2>Aluminum & Brass Construction<h2>How to Use</h2>Refer to FHC's Installation Instructions for Step by Step Installations Guidelines, Quick Metal Cutting Formula, and Glass Sizing Deductions. <h2>Included With</h2>Pacifica kits include head track, glass hangers, roller stops, floor guide, wall mount hangers, fixed panel glass attachments, threshold, and wall L-seal polycarbonate. NOTE: Handles, knobs, and bottom fixed glass panel hardware like u-channels or clamps are sold separately.

