



FHC Glendale Square 5 Degree Positive Close Wall Mount Hinge Full Back Plate

Item No. GLENF5

Features, Advantages, and Benefits

- Designed For 3/8"-1/2" (10 mm to 12 mm) Tempered Glass
- Solid Brass Construction

- Preset 5 Degree Pivot Pin
- Replacement Screws [PS102](#) and [PS103](#) are Available as Needed
- Can be used with Hinge Limit Plates [HLP25](#) and [HLP40](#)

Description:

Glass Specifications

MAXIMUM DOOR CAPACITY	3/8" (10 mm) GLASS	1/2" (12 mm) GLASS
	Approx. 5 lb./ft ²	Approx. 6.4 lb./ft ²
DOOR WEIGHT	DOOR WIDTH	
Using 2 Hinges	80 LBS (36 kg)	28" (711 mm)
Using 3 Hinges	120 LBS. (54 kg)	32" (813 mm)

NOTE: Do Not Exceed either maximum weight or width when choosing proper quantity of hinges.

Gasket Specifications

For 3/8" (10 mm) Glass: Use One Thick Gasket On Each Side For 1/2" (12 mm) Glass: Use One Thin Gasket On Each Side

Glass Instructions

Only use tempered safety glass. To prevent damage to the hinge finish during installation, do not use power tools when installing these hinges.

Overview

The Glendale Series Hinge has a dual degree pivot pin. It comes factory set at 90 degrees for normal door closing applications. There is also a secondary setting on the hinge pivot pin that can be field adjusted to allow an additional 5 degrees of closing for jobs that require a firmer positive position against a jamb or seal.

Care & Cleaning Guidelines

For best results, keep the following recommendations in mind when caring for your FHC shower door hardware. Your shower door should be dried daily with a soft towel or cloth to ensure its original finish. Do not use harsh cleaners or chemicals on the hardware, as many of the components are coated with a clear lacquer that will become damaged beyond repair. Always test your cleaning solution in an inconspicuous area prior to cleaning the entire hardware surface. Wipe surfaces clean using a soft, dampened cloth or sponge, and rinse completely with warm water immediately after applying the cleaning solution. Use only small amounts of liquid, gentle, cleaner. Never use abrasive products, sponges, or wire scrub brushes

while cleaning hardware.

Maintenance

FHC's hinges come factory greased for a silent, hassle-free experience. If there is any noticeable squeaking that occurs after installation it is recommended to apply a few drops of (3 in 1) multi-purpose oil to the hinge, at the nylon washer/pivot location. The lubricant will penetrate the hinge crevices, reducing friction, cleaning grime, and/or buildup. Spray lubricants are prohibited. If, for some reason, the hinge is disassembled during maintenance, use a small amount of white lithium grease to lubricate the interior



h HD S/S